

# XLT CUSTOM PROGRAM



**PROGRAM NAME**

DETECTOR MIKE - BM600

## BASIC ADJUSTMENTS

TARGET VOLUME	56
AUDIO THRESHOLD	23
TONE (AUDIO FREQ.)	226
AUDIO DISC.	ON
SILENT SEARCH	OFF
MIXED MODE	OFF
A.C. SENSITIVITY	70
D.C. SENSITIVITY	40
BACKLIGHT	0
VIEWING ANGLE	25

## PRO OPTIONS

<b>AUDIO</b>	
RATCHET PINPOINT	OFF
S.A.T. SPEED	7
TONE I.D.	OFF
V.C.O.	ON
ABSOLUTE VALUE	OFF
MODULATION	ON
<b>G.E.B. / TRAC</b>	
AUTOTRAC	ON
TRACVIEW	OFF
AUTOTRAC SPEED	16
AUTOTRAC OFFSET	+1
TRAC INHIBIT	ON

## DISCRIMINATION

<b>BLOCK EDIT</b>	
REJECT	-95 to -30
ACCEPT	-60 to +95
REJECT	to
ACCEPT	to
REJECT	to
<b>LEARN</b>	
LEARN ACCEPT	OFF
LEARN REJECT	OFF
RECOVERY SPEED	15
BOTTLECAP REJECT	2

## DISPLAY

VISUAL DISC.	ON
ICONS	OFF
V.D.I. SENSITIVITY	86
D.C. PHASE	OFF
GRAPH AVERAGING	ON
GRAPH ACCUMULATE	ON
FADE RATE	7

## PREAMP

TRANSMIT BOOST	ON
TRANSMIT FREQUENCY	4
PREAMP GAIN	7